



Adhesive tapes by Takis Lantzis & Sons

## **TECHNICAL INFORMATION**

**ADHESIVE TAPE: Masking Tape 80°C**

### **FILM PROPERTIES**

Type of Film	Impregnated Crepe Paper (White - Yellow)
Film Thickness ( $\mu\text{m}$ )	120 $\pm$ 20
Tensile Strength MD ( $\text{N}/\text{mm}^2$ )	55 $\pm$ 10
Elongation at Break MD (%)	9 $\pm$ 2

### **ADHESIVE PROPERTIES**

Type of Adhesive	Solvent-based, Natural Rubber
Colour	Transparent
Peel Adhesion ( $\text{N}/25\text{mm}$ )	4 $\pm$ 1
Shear Adhesion (h, 25mm x 25mm on cardboard, 23°C)	over 100
Rolling Ball Tack (cm)	under 2

Data stated above cannot be considered as binding by contract or by specifications. They correspond to the average values obtained from the tests carried out according to Atlas Tapes norms, in conformity with AFERA norms. Tests are carried out on samples taken from our standard production. These data may vary without any notice - the updated typical value sheets can be forwarded at any time. Since many different factors may influence the product's performance, we recommend to test the product by any application. We remain at your disposal for any further information or recommendations.

14 May 2009

**Athens office:** 68 Varis Av., Voula 166 73 Greece  
Tel: + 30 210 89 95 388 Fax Exports: +30 210 89 95 386  
**Atalanti factory:** 140km E75 Athens-Lamia Atalanti 35 200 Greece  
Tel: + 30 22330 23 725 Fax Exports: + 30 22330 23 756  
**Website:** [www.atlas-tapes.gr](http://www.atlas-tapes.gr)



**CERTIFICATE OF ANALYSIS**

**ADHESIVE TAPE: PP Solvent 28 mic Transparent**

<b>Date:</b>	03/11/08	<b>Customer: Sark Gulu</b>
<b>Customer O/N:</b>	682/2008	
<b>Atlas O/N:</b>	682/2008	

<u>Property</u>	<u>Typical Value</u>	<u>Result</u>
Type of Film	PP Transp	PP Trans
Film Thickness (microns)	28 + 10%	28.3
Type of adhesive:	Solvent based	Solvent based
Colour of adhesive:	Transparent	Transparent
Quantity of adhesive:	17 ± 2	18.1